

# DOJO

## Martial Arts & Combat Sports Matting

### PRODUCT DESCRIPTION

Superstrata Dojo is a specialist interlocking EVA foam mat system designed for martial arts studios, BJJ academies, boxing gyms, and combat sports training areas. The tatami-textured surface provides the grip and feel expected by practitioners, while the EVA foam core delivers the impact absorption required for throws, takedowns, and ground work. The interlocking jigsaw-edge system allows rapid installation and reconfiguration without tools or adhesive.

### TECHNICAL SPECIFICATIONS

| Property             | Value                                  | Test Standard |
|----------------------|--|---------------|
| Material Composition | EVA foam with tatami-textured surface  | —             |
| Tile Dimensions      | 1,000 × 1,000 mm                       | —             |
| Thickness Options    | 20mm, 40mm                             | —             |
| Surface Texture      | Tatami (traditional weave pattern)     | —             |
| Shock Absorption     | High (EVA foam core)                   | —             |
| Fire Classification  | To be confirmed                        | —             |
| Slip Resistance      | Dry slip resistance                    | —             |
| Installation Method  | Interlocking jigsaw edge (no adhesive) | —             |
| Warranty             | 5 years                                | —             |

### AVAILABLE FINISHES & DIMENSIONS

**Standard:** Black / Red reversible (two-colour tatami surface).

Tile size: 1,000 × 1,000 mm. Available in 20mm and 40mm thickness.

### RECOMMENDED APPLICATIONS

Martial arts studios (judo, BJJ, karate, MMA) · Boxing gyms · Wrestling rooms · Combat sports academies · School and university sports halls · Military hand-to-hand combat training areas · Gymnastics warm-up areas.

### NBS SPECIFICATION CLAUSE

# DOJO

Martial Arts & Combat Sports Matting

**Clause Reference: M50 / 130 — EVA Foam Matting, Martial Arts**

Supply and install Superstrata Dojo EVA foam matting to the areas indicated on drawings. Mats to be 1,000 × 1,000 mm, 20mm or 40mm thickness as specified, with tatami-textured reversible surface. Install using interlocking jigsaw-edge system without adhesive. Provide 5-year manufacturer's warranty on completion. Manufacturer: Superstrata Performance Flooring, [www.superstrata.fit](http://www.superstrata.fit)