

PADEL

Padel Court Modular Tile System

PRODUCT DESCRIPTION

Superstrata Padel is a specialist modular tile system designed and tested for padel court applications. The product meets the technical requirements of the World Padel Tour (WPT) and International Padel Federation (FIP) for court surface performance, including ball bounce consistency, slip resistance, and durability under intensive play. The interlocking tile system allows rapid court installation and is suitable for both indoor and outdoor padel court construction.

TECHNICAL SPECIFICATIONS

Property	Value	Test Standard
Material Composition	Polypropylene (PP) interlocking tiles	—
Tile Dimensions	330 x 330 mm	—
Thickness	14mm	—
Surface Texture	Textured for padel play	—
Ball Bounce Consistency	Meets FIP / WPT standards	—
Drainage	Open-grid design — self-draining	—
UV Resistance	Yes (outdoor grade)	—
Fire Classification	To be confirmed	—
Slip Resistance	Wet and dry slip resistance	—
Installation Method	Interlocking (no adhesive)	—
Warranty	5 years	—

AVAILABLE FINISHES & DIMENSIONS

Standard: Blue, Green, Red.

Tile size: 330 x 330 mm. Court line marking tiles available in White.

RECOMMENDED APPLICATIONS

Indoor padel courts · Outdoor padel courts · Padel club facilities · Hotel and leisure padel installations · Multi-sport facilities adding padel courts · Temporary and pop-up padel events.

PADEL

Padel Court Modular Tile System

NBS SPECIFICATION CLAUSE

Clause Reference: Q22 / 120 — Padel Court Surface, Modular Tile

Supply and install Superstrata Padel modular polypropylene court tiles to the padel court areas indicated on drawings. Tiles to be 330 x 330 mm, 14mm thickness, meeting FIP/WPT performance standards for ball bounce and slip resistance. Install using interlocking system without adhesive. Court line marking tiles in White as indicated on drawings. Provide 5-year manufacturer's warranty on completion. Manufacturer: Superstrata Performance Flooring, www.superstrata.fit