

STRIDE

Performance Rubber Roll Flooring

PRODUCT DESCRIPTION

Superstrata Stride is a continuous roll rubber flooring product designed for large-area installations where a seamless finish is preferred. Available in 8mm and 10mm thicknesses, it is manufactured from high-density recycled SBR rubber and supplied in 1.25m-wide rolls. Stride is ideal for cardio areas, running tracks, corridors, and machine zones where a smooth, uninterrupted surface is required. The product can be loose-laid or bonded with a suitable contact adhesive.

TECHNICAL SPECIFICATIONS

Property	Value	Test Standard
Material Composition	Recycled SBR rubber	—
Format	Roll (1.25m wide)	—
Thickness Options	8mm, 10mm	—
Surface Texture	Smooth / fine-grain	—
Fire Classification	Efl	EN 13501-1
Slip Resistance	Dry slip resistance	—
Installation Method	Loose lay or bonded with contact adhesive	—
Warranty	5 years	—

AVAILABLE FINISHES & DIMENSIONS

Standard: Pure Black

Roll width: 1.25m. Cut to length on site. Available in 8mm and 10mm thickness.

RECOMMENDED APPLICATIONS

Cardio zones · Treadmill and cross-trainer areas · Running track infields · Gym corridors and transition areas · Machine zones · Warm-up areas · Leisure centre general flooring.

NBS SPECIFICATION CLAUSE

STRIDE

Performance Rubber Roll Flooring

Clause Reference: M50 / 115 — Rubber Roll Flooring

Supply and install Superstrata Stride rubber roll flooring to the areas indicated on drawings. Roll to be 1.25m wide, 8mm or 10mm thickness as specified, manufactured from high-density recycled SBR rubber. Fire classification: Efl (EN 13501-1). Install by loose lay or bonded method as specified. Provide 5-year manufacturer's warranty on completion. Manufacturer: Superstrata Performance Flooring, www.superstrata.fit